



LISTING INFORMATION OF  
**McKeon - SafeSpace 500 Series Tornado & Hurricane  
Resistant Door**  
SPEC ID: 43799

McKeon Door Company  
44 Sawgrass Drive  
Bellport, NY 11713  
United States

**CONFIDENTIAL**  
**PROPERTY OF McKEON**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## LISTING INFORMATION

McKeon SafeSpace 500 Series Tornado & Hurricane Resistant Door

**CONFIDENTIAL**  
**PROPERTY OF McKEON**

### ICC-500-2014 PRODUCT ASSEMBLY & RATINGS

Assembly Type	Permitted Size	Tornado Resistance	Tornado Impact Rating
Roll-up Tornado Shelter Door	Min: 4'-4" wide* 4'-0" high  Max: 16'-4" wide 18'-0" high	+200/200 PSF  +252/-252PSF when limited to 4'4" wide doors	100 MPH 15 lbs.
Configuration  Mounted to the inside surface of a tornado shelter wall	Door: McKeon SafeSpace 500 Series Tornado & Hurricane Resistant Door  Upwardly acting roll-up door assembly with 3" steel slats and structural support guide system		

\*Width is tip to tip of support guide angles

Assembly Type	Permitted Size	Hurricane Resistance	Hurricane Impact Rating
Roll-up Hurricane Shelter Door	Min: 4'-4" wide* 4'-0" high  Max: 16'-4" wide 18'-0" high	+200/200 PSF	100 MPH 9 lbs.
Configuration  Mounted to the inside surface of a Hurricane shelter wall	Door: McKeon SafeSpace 500 Series Tornado & Hurricane Resistant Door  Upwardly acting roll-up door assembly with 3" steel slats and structural support guide system		

\*Width is tip to tip of support guide angles

Attribute	Value
Certificate Date of Expiry	April 23, 2025
Certificate Date of Initial Registration	April 23, 2020
Certificate Number	WHI20-20384307
Criteria	FEMA 361
Criteria	ICC-500 (2014)

CSI Code	08 34 00 Special Function Doors
Intertek Services	Certification
Issue Status	1
Listed or Inspected	LISTED
Listing Section	WIND LOAD RESISTANT DOORS
Report Number	H5680, F3964, E2664, G10337886,
Spec ID	43799
Test Original Issue Date	April 9, 2015
Verification Testing	No
Windload/Structural	Storm Shelter
Windload/Structural	Tornado Resistance

**CONFIDENTIAL**  
**PROPERTY OF McKEON**