SpecDIRECT™ POWERED BY **intertek**

intertek
Total Quality. Assured.

LISTING INFORMATION OF

McKEON MCK3200 and MCK4415 Curtain Fabrics

SPEC ID: 68225

McKEON
44 Sawgrass Drive
Bellport, NY 11713
United States

LISTING INFORMATION

The MCK3200 and MCK4415 curtain fabrics are used in the construction of McKEON Smoke and Draft and/or Fire Protective curtain assemblies. Material properties and flame spread ratings for each fabric are detailed below.

MATERIAL PROPERTIES - MCK3200

Material Property	Description
Finished Weight	13.4 oz/yd^2 (455 g/m^2)
Finished Thickness (nominal)	16 mils (0.40 mm)
Base Fabric	Fiberglass
Weave	4 Shaft Satin
Warp & Weft (1/cm)	18.6 x 11
Finishing/Coating	Aluminum pigmented polyurethane
ASTM E84 Flame Spread Index (FSI) ASTM E84 Smoke Developed Index (SDI)	<25 <450

MATERIAL PROPERTIES - MCK4415

Material Property	Description
Finished Weight	18.9 oz/yd^2 (640 g/m^2)
Finished Thickness (nominal)	21 mils (0.54 mm)
Base Fabric	Stainless steel reinforced fiberglass
Weave	8 Shaft Satin
Warp & Weft (1/cm)	16 x 15.3
Finishing/Coating	Aluminum pigmented polyurethane
ASTM E84 Flame Spread Index (FSI) ASTM E84 Smoke Developed Index (SDI)	<25 <450

Attribute	Value
Criteria	ASTM E84 (2021)
CSI Code	07 80 00 Fire and Smoke Protection
CSI Code	07 87 00 Smoke Containment Barriers
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	SPECIALTY FIRE/DOOR & FRAME ASSEMBLIES & COMPONENTS
Spec ID	68225